

DATASHEET

VALVE SENSE INSPECTION



APPROVALS



ATEX approval: EX-Zone 1/21
 Ⓜ II 2G Ex ib IIC T4 Gb
 Ⓜ II 2D Ex ib IIIC T135°C Db



IECEX approval: EX-Zone 1/2
 Ex ib IIC T4 Gb
 Ex ib IIIC T135°C Db



NEC500 approval
 Class I Div. 1 Groups A, B, C, D, T4
 Class II Div. 1 Groups E, F, G, T135°C
 Class III Div. 1



KCs approval
 Ex ib IIC T4
 Ex ib IIIC T135°C

IS540.1 SMARTPHONE

TECHNICAL FEATURES SMARTPHONE MODEL M540A01

Operating system	Android™ 14
Processor	Qualcomm QCM6490
Memory	8 GB RAM 128 GB internal memory microSD memory up to 128 GB
Supported frequency bands	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 MFBI B13/14/17/20/25/26/28/29/30/66/71 4G LTE-TDD: B38/39/40/41/42/43/48 5G NR: n1/n2/n3/n5/n7/n8/n12/n20/n25/n28/n30/n38/n40/n41/n48/n66/n71/n77/n78/n79
Dimensions	Size: 180,0 x 84,9 x 20,6 mm weight: 422 g
Display	6" Gorilla Glass® 3rd generation 1080 x 2160 pixels FHD
Battery	4400 mAh replaceable
Camera	48 MP AF rear camera 5 MP FF front camera
SIM support	1 nano SIM + eSIM
Connections	Wi-Fi 6: IEEE 802.11 a/b/g/n/ac/ax/e/k/r/v Bluetooth® 5.2 GPS, A-GPS, Glonass, A-Glonass, Beidou, Galileo Near Field Communication (NFC)
Ports in/out	16-pin ISM interface USB-C
Sensors	Accelerometer, Gyroscope, Light, Magnetic, Proximity, Pressure sensors
Types of protection	IP68 dust-/waterproof MIL-STD-810H usable from -20 °C to +55 °C



IS-VS1A.1 INSPECTION EQUIPMENT

TECHNICAL FEATURES MEASURING ELECTRONIC MODEL MVS1A01

Analog band width	20 ... 500 kHz
Input range	94 dBAE / 100 dBAE
Sampling rate	Res.: 2 MHz / 16 bit
Noise floor	<12 µVRMS (95 – 300 kHz)
Power consumption	<700 mW
Dimension	Size: 141,2 x 96,0 x 51,85 mm weight: 219,3 g
Operating temperature	Usable from -20 °C to +55°C



Please visit our website and you will find more information of our devices.

TECHNICAL FEATURES SENSORS

IS-SU150F1.1	Sensor Ultrasonic	
Frequency range	100 - 450 kHz	
Operating temperature	-40 °C ... + 120 °C	
Connector	SMB	
Shield Cross-Talk	> -80 dB	
Dimension	22,3 x 18,2 mm	
Weight	29 g	
IS-SU150F2.1	Sensor Ultrasonic	
Frequency range	100 - 450 kHz	
Operating temperature	-40 °C ... + 120 °C	
Connector	SMB	
Shield Cross-Talk	> -80 dB	
Dimension	22,3 x 37,5 mm	
Weight	63,4 g	
IS-SU030F2.1 (optional)	Sensor Ultrasonic	
Frequency range	25 - 80 kHz	
Operating temperature	-40 °C ... + 120 °C	
Connector	SMB	
Shield Cross-Talk	> -80 dB	
Dimension	22,3 x 37,5 mm	
Weight	64 g	
IS-SC120BB1.1	Sensor Cable	
Length	120 cm	2 pcs. / Set
Connector	SMB <-> SMB	
Sheathing	Braided hose	
Temperature range	-20 °C ... +60 °C	
Weight	20 g (each)	



TECHNICAL FEATURES WAVEGUIDE

IS-WGLF1.1	Waveguide Lock	
Diameter	55 mm	Waveguide Lock; fixation for sensor F1" indicates used sensor
Weight	79,5 g	
IS-WGxx.1	Waveguide	
Temperature range	> 120 °C and < -50 °C	
Dimension	220 x 7 mm	
Weight	89,8 g	



SET CONTENT

Measuring electronic IS-VS1A.1, Sensor IS-SU150F1.1, Sensor IS-SU150F2.1, Waveguide Lock IS-WGLF1.1, Waveguide IS-WGxx.1, 2 x Sensor Cable, Coupling medium, Coupling film, IS540.1 Smartphone, Battery, i.safe PROTECTOR 2.0 Type C USB Cable, Power Adapter universal, Screwdriver, Display Protection Foil, Display Cleaning Cloth, Quick Start Manual and Safety Instructions, Case

Please visit our website and you will find more information of our devices.